

RDA Solutions batteries use high purity raw materials and low density electrolytes to produce superior cycle performance and low self-discharge rate. Our batteries are specifically designed to withstand harsh environments.

► Specification

Cells Per Unit	6
Voltage Per Unit	12
Capacity	26Ah @ 20hr-rate to 1.75V per cell @25°C (77°F)
Weight	Approx. 8kg(17.6 lbs)
Maximum Discharge Current	420A(5sec)
Internal Resistance	Approx. 9.5 mΩ
Operating Temperature Range	Discharge: -15°C~50°C (5°F~122°F) Charge: -15°C~40°C (5°F~104°F) Storage: -15°C~40°C (5°F~104°F)
Nominal Operating Temperature Range	25°C±3°C (77°F±5°F)
Float Charging Voltage	13.5 to 13.8 VDC/unit Average at 25°C (77°F)
Recommended Maximum Charging Current Limit	8.4A
Equalization and Cycle Service	14.4 to 15.0 VDC/unit Average at 25°C (77°F)
Self Discharge	RDA Solutions batteries can be stored for more than 6 months at 25°C (77°F). Please charge batteries before using. For higher temperatures the time interval will be shorter.
Terminal	Thread lead alloy recessed terminal to accept M5 or M6 bolt
Container Material	ABS(UL 94-HB) & Flammability resistance of (UL 94-V0) can be available upon request.




IT1720HL22031803

VRLA batteries are certified by ISO 9001, ISO14001 and OHSAS18001.

► Dimensions :

Unit: mm	Overall Height (H)	Container height (h)	Length (L)	Width (W)
	127±1.5	127±1.5	165±1.5	175±1.5



Constant Current Discharge Characteristics Unit:A (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	90.2	51.5	29.6	16.34	6.89	4.704	2.650	1.421
1.67V	88.4	50.1	29.3	16.15	6.84	4.667	2.639	1.415
1.7V	87.3	49.2	29.1	16.03	6.81	4.641	2.631	1.412
1.75V	83.0	47.0	28.5	15.62	6.69	4.564	2.604	1.400
1.8V	74.6	43.4	27.4	14.89	6.45	4.425	2.548	1.372
1.85V	57.9	36.6	25.3	13.62	5.88	4.119	2.408	1.316

Constant Power Discharge Characteristics Unit:W (25°C, 77°F)


F.V/Time	5min	15min	30min	1h	3h	5h	10h	20h
1.60V	154.5	98.4	57.1	31.06	13.59	9.180	5.215	2.815
1.67V	147.6	93.7	56.7	30.78	13.47	9.142	5.187	2.807
1.7V	142.8	90.5	56.4	30.61	13.40	9.105	5.172	2.802
1.75V	130.5	83.7	55.4	30.12	13.17	8.961	5.107	2.780
1.8V	112.5	74.5	53.3	29.13	12.70	8.662	5.001	2.726
1.85V	87.6	62.6	49.2	27.07	11.70	8.200	4.763	2.625




Trickle(or Float)Design Life




Capacity Retention Characteristic




Battery Voltage and Charge Time for Standby Use




Cycle Service Life



Battery Voltage and Charge Time for Cycle Use



Terminal Voltage (V) and Discharge Time



Charging Procedures

Application	Charge Voltage(V/Cell)			Max.Charge Current
	Temperature	Set Point	Allowable Range	
Cycle Use	25°C(77°F)	2.45	2.40~2.50	0.3C
Standby	25°C(77°F)	2.275	2.25~2.30	

Discharge Current VS. Discharge Voltage

Final Discharge Voltage V/Cell	1.75	1.70	1.65	1.60
Discharge Current(A)	0.2C>(A)	0.2C<(A)<0.5C	0.5C<(A)<1.0C	(A)>1.0C

Effect of temperature on capacity (20HR)

Temperature	Dependency of Capacity (20HR)
40 °C	102%
25 °C	100%
0 °C	85%
-15 °C	65%

Self-discharge Characteristics

Storage time	Preservation rate
3 Months	91%
6 Months	82%
12 Months	64%

